

# So what's Unique about ArmourLux500 iPPRO ?

A competitively priced, high fibre density - up to 24 fibres - per connector with Tactical deployable fibre, where high cable retention and durability are important. When mated the connector is locked and offers IP68 protection to keep out water and dust. You can hook up to a bulkhead or a fanout cable to convert to standard connectors if preferred. The Military grade Tactical fibre manufactured by Belden & OCC is durable and suited to repeated retrieval and deployment.

# **Buy with Confidence**

All ArmourLux assemblies are made in the UK. We're also an ISO9001 accredited company, where quality and customer service are our highest priorities. With over 25 years experience as a trusted provider of fibre optic cables, you can be reassured we understand the requirements of mobile fibre optic communications.



















#### The ipprovi Connector

Available in 2, 12 and 24-fibre connectors, we also offer a 4 fibre option using two IP-PRO2 plugs.







RO 2 IP-PRO 12/24

IP68 Cap & Tether

## Capacity per Reel (m)

|        | Number of Fibres | 2     | 4     | 8     | 12    | 24    |
|--------|------------------|-------|-------|-------|-------|-------|
|        | Cable Diameter   | 5.4mm | 5.8mm | 6.4mm | 7.3mm | 8.5mm |
|        | R1               | 76m   | 67m   | 49m   | 36m   | 33m   |
|        | R2               | 141m  | 123m  | 90m   | 66m   | 61m   |
| OPTION | R3               | 277m  | 241m  | 177m  | 129m  | 120m  |
|        | R9               | 447m  | 390m  | 286m  | 209m  | 194m  |
| REEL   | R10              | 710m  | 618m  | 454m  | 331m  | 308m  |
|        | R6               | 906m  | 847m  | 622m  | 453m  | 422m  |
|        | R7               | 1359m | 1270m | 933m  | 680m  | 633m  |

#### Cable Comparison

| Number of Fibres  | 2                                  | 4     | 8     | 12    | 24    |  |
|---|------------------------------------|-------|-------|-------|-------|--|
| Cable Diameter  | 5.4mm                              | 5.8mm | 6.4mm | 7.3mm | 8.5mm |  |
| Weight/km   | 26kg                               | 30kg  | 37kg  | 45kg  | 55kg  |  |
| Tensile Strength Short<br>Term<br>Operating Temperature | 300N                               | 400N  | 400N  | 450N  | 450N  |  |
| Operating Temperature                                   | -55°C to +85°C                     |       |       |       |       |  |
| Crush Long/Short Term                                   | 3000N/m / 5000N/m (IEC 60994-2-20) |       |       |       |       |  |

### **Features**

- 2, 12 and 24 fibres per connector
- IP68 protected from dust and water
- Quality Belden Tactical fibre cable
- Compact, high capacity reels
- Made from lightweight PBT
- Range of IP68 chassis connectors
- Available in both multi and single mode
- Snag-free protective cap
- Excellent cable retention
- Lightweight and easy to carry
- Manufactured in the UK
- Aftersales refurbish and repair service

50c

To see our other range ArmourLux cable ranges, to request an ArmourLux sample or for more information, please call: 01488 685 800 or email: info@armourlux.com



ArmourLux is a brand of Universal Networks UK Limited
Charnham Lane, Hungerford, Berkshire RG17 0EY.
T: +44 (0) 1488 685800 | F: +44 (0) 1488 685899 | www.armourlux.com